

PRODUCT DATA SHEET

FASSON®

FASSON® Crack-Back® Plus Coverall

issued: March 2011

Introduction

A self-adhesive paper sheet product for offset printing combined with the unique, diagonal Crack-Back Plus backing removal system.

Description

Face : A fully-opaque premium-quality cast-coated woodfree paper, mirror finished glossy surface, white
Adhesive : Permanent
Backing : Crack-Back Plus

Printing & Conversion

Offset printing.

Before applying the label, the surface must be clean, dry and grease-free (*see technical bulletin 7.1*).

Features

Excellent layflatness, enabling high speed printing.

The unique Crack-Back Plus backing removal system with diagonal scored lines facilitates creating lay-outs, conversion and application of the label.

Product has excellent correction-, overposting- and block-out characteristics

Uses

Correction-, cover-up-, overposting-, block-out- and packaging labels/stickers with a *gloss* finish; on flat or curved surfaces.

For indoor use only.

General

Shelf life : 2 years stored at 20°C / 55% R.H.
Total caliper (±10%) : 197 micron



www.averygraphics.com

Graphics & Reflective Products Division
Rijndijk 86, P.O. Box 118
2394 ZG Hazerswoude – The Netherlands
Tel +31 71 3421500 – Fax +31 71 3421538

PRODUCT CHARACTERISTICS

Fasson® Crack-Back® Plus Coverall

Physical properties

Face

Basis weight	: 94 g/m ²	ISO 536
Caliper	: 85 micron	ISO 534
Tensile	: 680 mN MD	DIN 53115
Tear (Elmendorf)	: 700 mN MD	DIN 53115
Opacity	: 100 %	ISO 2471

Adhesive

Permanent : General-purpose emulsion-based permanent adhesive with a high initial tack and high adhesion on most common substrates

	<u>Permanent</u>	
Minimum application temperature	+5 °C	
Service temperature range	-40 °C to +80 °C	
Adhesion on stainless steel, initial	350 N/m	FTM-2
Quick Stick on glass	430 N/m	FTM-9

Backing

Crack-Back Plus : One-side-coated bleached kraft paper, with **diagonally** crush-scored lines, along which the backing will crack cleanly when bent back, allowing easy removal in just two pieces. Lines are spaced just **32 mm** apart. Good layflatness ensures first-class printing and finishing. (*For optimal functionality take care of the following: minimum label size must be 20 cm². The shortest side of a rectangle or the smallest diameter of an ellipse must be at least 25 mm.*)

	<u>Crack-Back Plus</u>	
Basis weight	94 g/m ²	ISO 536
Caliper	95 micron	ISO 534

Warranty: FASSON® brand products are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge.

Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing. All FASSON® brand products are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

Important: Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change without notice. In case of any ambiguities or differences between the English and foreign versions of these Conditions, the English version shall prevail.

March 2011

