
Fasson® 2.6 Mil White BOPP NTC/S692N/40#BG**Spec# 76912 - Splice-Free****Facestock:**

Fasson® 2.6 Mil White BOPP is a corona treated white biaxially oriented polypropylene film for rigid containers.

| | |
|---------------|--|
| Basis Weight: | n/a |
| Caliper: | 0.0026 inches \pm 10% |
| Tensile: | MD 13,500 psi (target) CD 27,500 psi (target) |
| Tear: | n/a |
| Stiffness: | MD 20 mg (target) |

Adhesive:

Fasson® S692N is a clear general purpose permanent acrylic adhesive. It exhibits a balance of high cohesive strength and adhesion to low surface-energy substrates for lasting performance on squeezable containers. Specifically designed to exhibit excellent wetout characteristics and short-term removability. Meets the requirements of FDA 21 CFR 175.105 for indirect food contact. This section covers applications where incidental contact between food and adhesive could occur.

| | |
|----------------------------------|--|
| Type: | Emulsion acrylic |
| Minimum Application Temperature: | +23°F |
| Service Temperature Range: | -20°F to +200°F subject to facestock limitations |

Typical Performance Data: 2 Mil Clear Polypropylene facestock at room temperature on standard lab panels.

HDPE

| | |
|----------------|---------------|
| Loop Tack: | 1.2 - 1.8 lbs |
| Peel Adhesion: | 1.1 - 1.7 lbs |

PET

| | |
|----------------|---------------|
| Loop Tack: | 3.6 - 4.2 lbs |
| Peel Adhesion: | 2.6 - 3.2 lbs |

Glass

| | |
|----------------|---------------|
| Loop Tack: | 2.6 - 3.2 lbs |
| Peel Adhesion: | 1.6 - 2.2 lbs |

Liner:

Fasson® 40#BG is a bleached glassine white liner with excellent roll label converting properties. Designed for low-to medium-speed dispensing applications. Not recommended for sheeted applications. Features good back printability.

| | |
|---------------|--|
| Basis Weight: | 40# per ream \pm 10% (500 sheets 24" x 36") |
| Caliper: | 0.0023 inches \pm 10% |
| Tensile: | MD 36# per inch width CD 19# per inch width |
| Tear: | MD 36 grams CD 39 grams |

Total Construction Caliper (approximate): 0.0057 inches \pm 10%

Shelf Life

Unless specified otherwise in this document, one year when stored at 72°F at 50% RH

Statement of Practical Use

All materials, sales and contracts for sale of Avery Dennison products are sold with the express requirement and understanding that the customer is solely and exclusively responsible for testing and for ensuring the products are fit for the customer's purposes or an end-user's purposes. All express or implied warranties of merchantability and fitness for particular use are disclaimed.

Warranty

All sales and contracts for sale are expressly conditioned on the buyer's assent to Avery Dennison's terms and conditions found on its website at www.na.fasson.com. Avery Dennison hereby objects to any term, different from or additional to Avery Dennison's terms, contained in any buyer communication in any form, unless agreed to in a writing signed by an officer of Avery Dennison.

www.na.fasson.com



Label and Packaging Materials -North America

8080 Norton Parkway
Mentor, OH 44060
800-944-8511

